



Stonewall[®] Collection



Stonewall
Straight Face



Stonewall
Curved Face



Tumbled
Stonewall SF



Stonewall® Collection

INTRODUCTION

Our Stonewall Collection offers a stylish alternative to natural stone walls at a substantial savings. Available with a curved or straight traditional split-face or a tumbled texture, the Collection embodies the look of natural quarried stone and the core design provides reliable and cost-effective performance, block after block. Stonewall Collection is available in a variety of classic solid colors and natural blends.

COMPOSITION & PERFORMANCE

The Stonewall Collection offers dependable strength and lasting durability. Manufactured under controlled factory conditions, each unit is comprised of a cement-rich mixture blended with select aggregates and pure iron oxide pigments molded under extreme pressure and vibration. The Tumbled SF Stretcher undergoes our genuine Drum-Roll Tumbled® process that imparts a “stone-rocked” finish and unique character to each piece, while preserving the structural integrity and dimensional stability found throughout our entire line of retaining wall systems.

The Stonewall Collection features a hollow core design. When filled with aggregate, the stone creates a positive “rock lock” connection between units and also secures geogrid in reinforced engineered walls. The stone-filled cores allow for drainage and serve to protect against the negative effects of water build-up and hydrostatic pressure.

The Stonewall Collection can be used for a variety of applications such as ■ straight, curved and serpentine retaining walls ranging from planter height to tall commercial walls ■ stairs ■ corners ■ pillars and ■ terraced walls. For most non-critical walls under 4' high, Stonewall is constructed as a gravity wall. When engineered using geogrid, it functions as a highly-effective system for tall and structural walls.

TECHNICAL SERVICES

We offer a variety of services, information and literature, including estimating charts, WSB Analysis and Design software and SRW's free Preliminary Design Service. When needed, we also can provide the name of a professional engineer. Please contact your Authorized Dealer or Ideal's Sales Office for information. Design consultation, specification assistance, and job-site quality review can be provided upon request.

A white deposit known as efflorescence may appear naturally on any concrete or masonry product. It does not affect the structural integrity and will dissipate over time. Efflorescence is not indicative of a flawed product. For more information, please ask for our Efflorescence Advisory.

Stonewall® is a registered trademark of Westblock Systems

©2006-2016

PHYSICAL CHARACTERISTICS

The Stonewall Collection meets or exceeds North American industry standards, including NCMA Tek 2-4B and/or ASTM C 1372 Specification for Segmental Retaining Wall Units with respect to compressive strength, density and absorption. Strict quality control ensures consistent strength and durability for years of easy care and lasting beauty.

Curved Face Stretcher	8"h x 12"w x 12"d • 50 lb
Straight Face Stretcher	8"h x 12"w x 12"d • 54 lb
Tumbled SF Stretcher	8"h x 12"w x 12"d • 54 lb
Coverage	1.5 pcs per sf
Corner/Half Reversible	8"h x 6"w x 12"l • 35 lb

Universal Coping	3¾"h x 16"l x 13"d
Roman Pisa Coping	3¾"h x 16"l x 13"d
Ancestral Coping (2pc set)	3¾"h x 16"/13"l x 13"d 3¾"h x 13"/10"l x 13"d

Setback: ½" per course and ¾" (4.5°) per vertical foot
Minimum Diameter: 3' to face of block
Compressive Strength: 4500 psi minimum
Water Absorption: 8% maximum
Freeze Thaw: Little or no effect

GENERAL INSTALLATION GUIDELINES

Designers, professional contractors and d-i-y homeowners alike will enjoy the commercial-grade, structural performance of our Stonewall Collection. The easy to handle weight results in superior productivity with less fatigue and strain. Placing Stonewall, even onto courses above waist level, is easily accomplished, unlike wall systems comprised of heavy block units that often require equipment or two people to lift and place the unwieldy units.

The Stonewall Collection employs a pin and channel alignment system. The notched channel molded into the bottom of each block helps guide the units onto the strong nylon pins that align the units and automatically create a batter as the blocks are stacked together. For complete details and guidance on installation, we invite contractors to refer to our Contractor's Guide to Installing Segmental Retaining Wall Systems. Homeowners, be sure to ask your Ideal Authorized Dealer for our Ideal Way to Build Walls with Style using Stonewall pamphlet. It provides easy to follow instructions that will guide you step-by-step, from start to finish.

Important! Walls 4' and higher, terraced walls, sites with weak or wet soils, slopes and other loading conditions, such as a driveway above the wall, require special considerations and construction techniques, including the use of geogrid. We recommend you use a qualified soils engineer and a professional contractor for these situations. Always check with your local building department for code requirements before building a retaining wall. Safety is key!

45-55 Power Road, Westford, MA 01886
232 Lexington Street, Waltham, MA 02452

Main Phone: (781) 894-3200 • Main Fax: (978) 692-0817
www.IdealConcreteBlock.com

