

NEW SONIC SYSTEM

FORESTRY MULCHERS FOR SKID STEERS

UML/SSL/VT

Forestry mulcher with fixed tooth rotor for excavators.



75-120 hp



∅ 8 in max



STANDARD EQUIPMENT

110/60cc variable torque hydraulic piston motor (32-53 gpm)	Hydraulic front hood
Safety and anticavitation valve	Adjustable skids
Enclosed / anti dust machine body	Working pressure control gauge
Motor enclosed in the frame	Guard frame
Belt transmission	Dual row protection chains
Poly Chain Belt Transmission	Welded counterblades
Hydraulic hoses	

OPTIONS

Customized setting hydraulic motor	Multiple tooth options
Diverter valve (plug in and play)	Rotor Bite Limiter
Oil cooler kit	Sonic System
Case drain required	

MODEL	UML/SSL/VT 125*	UML/SSL/VT 150*	UML/SSL/VT 175*
Power (hp)	75-120	75-120	75-120
Flow rate (gal/min)	32-53	32-53	32-53
Pressure (PSI)	2900-5000	2900-5000	2900-5000
Working width (in)	53	62	72
Total width (in)	65	74	83
Weight (lbs)	2646	2866	3086
Rotor diameter (in)	16.5	16.5	16.5
Max shredding diameter (in)	8	8	8
No. teeth type C/3+C/3/SS	26+2	32+2	36+2
type I+C/3/SS	36+2	42+2	50+2

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.

*Variable displacement hydraulic motor.

ROTOR TYPE C



C/3
(standard)



C/3/HD
(option)



BL Blade
(option)



K/3
(option)

ROTOR TYPE I



I
(option)



C/3/SS
(side scraper)