All pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.

FORESTRY MULCHERS FOR SKID STEERS

UML/SSL/VT/BL

Forestry mulcher with Bite Limiter rotor system



75-120 hp



Ø8 in max



STANDARD EQUIPMENT	
110/60cc variable torque hydraulic piston motor (32-53 gpm)	Adjustable skids
Safety and anticavitation valve	Working pressure control gauge
Enclosed / anti dust machine body	Guard frame
Motor enclosed in the frame	Dual row protection chains
Belt transmission (Poly Chain)	Welded counterblades
Hydraulic hoses	Rotor Bite Limiter

OPTIONS		
Customized setting hydraulic motor	Sonic System	
Oil cooler kit		
Case drain required		

MODEL	UML/SSL/VT/BL 125	UML/SSL/VT/BL 150	UML/SSL/VT/BL 175
Power (hp)	75-120	75-120	75-120
Flow rate (gal/min)	32-53	32-53	32-53
Pressure (PSI)	2900-5000	2900-5000	2900-5000
Working width (in)	53	62	72
Total width (in)	65	74	83
Weight (lbs)	2646	2866	3086
Rotor diameter (in)	16.5	16.5	16.5
Max shredding diameter (in)	8	8	8
No. blades type C/3+C/3/SS	20+2	24+2	30+2

Data refers to machine as standard set-up. Options may have reflects on weights and dimensions. The technical data in this catalogue may be altered without prior notice.

ROTOR TYPE C





